

ELECTRICAL SAFETY
POWER QUALITY
ENERGY MANAGEMENT



GRAPHENE POWER METER - GPM96

Power Quality & Energy Meter

- Complies with IEC62053 class 0.5S
- Measurement sampling rate of 128 samples/cycle
- Built-in Modbus RTU communication (optional TCP/IP)
- Measures harmonics up to 63rd order

GPM96 - Power Quality & Energy Meter



Product Description

The GPM96 is part of the new smart Graphene-Meter-Series. The unit measures all-important system values like voltage, frequency, power, power factor, THDV, THDI harmonics (up to 63rd), displacement power factor, voltage crest factor, current K-factor, or voltage unbalance. The built-in Modbus RTU (Optional TCP/IP) interface ensures smooth communication to any other system.

Together with an accuracy class of CI 0.5S (IEC62053-22) makes the GPM96 an allrounder and an ideal choice for any analysis in all kinds of electrical systems.

Features

- Accuracy according to IEC62053-22 CI 0.5S
- Instantaneous values, L-N voltage, L-L voltage, frequency, power, power factor, THDV, THDI harmonics, Displacement Power Factor (option), voltage crest factor (option), Current K factory (option), voltage unbalance (option)
- Harmonics up to 15th order (Optional up to 63rd order)
- Memory Recording for energy, demand, max demand & max/min record
- Real time clock
- Built-in Modbus RTU Communication
- 6.4kHz sampling (128 Samples/cycle)
- Multi tariffs
- Optional - 4DI, 2DO
- Optional - Modbus TCP/IP
- Optional - MID certified

Typical Applications

- Low voltage distribution networks
- Power station
- Generation plant
- Data Center
- Consumer billing
- Retails shop
- Commercial/residential building
- Oil & Gas Plant
- Offshore and marine
- High tension distribution network

Certifications & Compliances



Technical Specification

Power Supply

Rated Voltage	AC85 ~ 275Vac /DC120~380Vdc
Power Consumption	≤7VA
Withstand voltage	≥2kV

Communication / Interface

RS - 485: Modbus-RTU

Physical interface	RS-485
Communication speed	Up to 38.4 kbps
Communication protocol	Modbus-RTU
Isolation voltage	2000 VAC(1 min)

Relay output

Capacity	3A/250 VAC
----------	------------

Isolation voltage	Between contact and coil: 2500 VAC/min
-------------------	--

Output Frequency	1 Hz maximum
Relay Type	Electromagnetic relay
Compliance	Electrostatic Discharge IEC61000-4-2

Energy pulse output (GPM96-MID only)

Pulse width	Selectable 200/100/60 ms
Pulse Output	kWh/kVarh
Pulse constant	0.001/0.01/0.1/1/10/100/1000 per pulse
Compliance	IEC62053-31 Class A.

Digital input

Number	4 (max) ** Optional
Isolation voltage	2500 VAC(1 min)
Response Time	10 ms
Maximum Frequency	1kHz

Measuring circuit

Measuring voltage inputs

Rated range (PK Series, 3P4W)	400 VAC L-N (690 VAC L-L)
Rated range (PK Series, 3P3W)	400 VAC L-L
Resolution	0.1 V
Impedance	1.6 MΩ/per phase
Power consumption	≤0.1 VA /per phase
Over voltage	As per IEC61010-1 CAT III
Frequency	45-65 Hz

Measuring current inputs

Rated range	5A/1A, (continuous: 1.2In)
Resolution	5 mA
Impedance	≤20mΩ/per phase
Power consumption	≤0.2 VA/per phase
Over current	120A for 0.5Seconds

Product is tested and manufactured according to...

Electrostatic discharge immunity	IEC61000-4-2
Radiated, radio-frequency, electromagnetic field immunity	IEC61000-4-3
Electrical fast transient/burst immunity	IEC61000-4-4
Surge immunity	IEC61000-4-5
Immunity to conducted disturbances, induced by radio-frequency fields	IEC61000-4-6
Power frequency magnetic field immunity	IEC61000-4-8
Immunity to Voltage Dips	IEC61000-4-11
Radiated Emissions	EN55011 Class A
Harmonics	IEC61000-3-2

Working Environment

Working temperature	-25°C to 55°C
Storage temperature	-40°C to 70°C
Relative humidity	≤95%RH, no condensation
Working altitude	≤2000m
Protection degree	Front case IP54, rear case IP20
Pollution	Degree II

Measurement Parameters

Power Quality Analysis

Sampling	128 points/cycle wave
Harmonic	2~63rd Harmonic,
Sequence of events	20 events

Phase Sequence	Yes
Displacement Power factor	Modbus read
Voltage crest factor	Modbus read
Current Kfactor	Modbus read
Threshold setting	Trigger DO
Phase Angles	3 Phase Voltage / 3 Phase Current
Real-time Data	Voltage, Current, Active power, Reactive power, Apparent Power, Power Factor, Frequency
Measurement Channel	3 channel for each: Voltage / Current

Energy

Energy	Positive / Negative active, reactive, apparent energy ; Positive / Negative base wave active, reactive energy
Multi-tariff energy	4 tariff, 8 time period

Demand

Real-time Demand	fixed- and slide window record value
------------------	--------------------------------------

Accuracy

Voltage/ Current	±0.2%
Re-, Active/Apparent power	±0.2%
Active Energy	IEC62053-22 Class 0.5S, IEC61557-12 Class 0.5
Reactive Energy	IEC62053-23 Class 2, IEC61557-12 Class 2
Power Factor	±0.01
Frequency	±0.1%


Memory

Memory	120 KB
--------	--------

Dimensions & Ordering Code


Ordering Code for GPM96-Series

G	Eetarp Product Fixed Code
A	A = IEC62053-22, M = MID Class
X	Reserved
X	Reserved
X	Reserved
X	C = MODBUSRTU, E = MODBUSTCP/IP
X	B = Aux 65~480V AC/ 80~660V DC, C = 24~48V DC, D = Self-power supply
X	5 = RS485, 6 = TCP/IP
X	Reserved
X	3 = Demand Version + 15th harmonics version 4 = Demand + Min/Max + 63 rd Harmonics Version + multi tariffs + DPF+ Unbalance 5 = Basic Version 6 = MID, Multi-tariff with 63 rd Harmonics Version
X	X = No Ethernet Gateway, 1 = With Ethernet Gateway
X	2 = No DI/DO, 3 = 4 DI & 2 DO
X	X = No Pulse Outputs, 2 = 2 Pulse Outputs
X	Reserved
X	X = 1% - Basic version 0 = 0.5% 1 = 0.2%



Common GPM96 Variants

Order Number	Type	Features
GMXXCD5X6X22X0	GPM96-MID	GPM96 with 63 rd harmonics, Multi Tariffs, Modbus RS485, MID Certified, 2 pulse output
GAXXC5X5X2XX0	GPM96-PK2	GPM96 with basic electrical parameter, Modbus RS485, CL0.5S
GAXXC5X4X2XX0	GPM96-PK3	GPM96 with 63 rd harmonics, Multi Tariffs, Modbus RS485, min/max, CL0.5S (Basic Model)
GAXXC5X4X3XX0	GPM96-PK4	Basic Model + 4xDI, 2xDO
GAXXE6X4X2XX0	GPM96-PK5	Basic Model + Modbus TCP/IP
GAXXE6X4X3XX0	GPM96-PK6	Basic Model 4xDI, 2xDO, Modbus TCP/IP
GAXXE6X413XX0	GPM96-PK7	Basic Model 4xDI, 2xDO, Modbus TCP/IP, Modbus Gateway



Eetarp Engineering Pte Ltd

1 North Coast Avenue, #03-01
Singapore 737663
Tel: +65 6339 3651
Fax: + 65 6339 3667
Email: contact@eetarp.com
Website: www.eetarp.com
CRN: 200001617K

Supported Countries

Australia, China, India, Indonesia, Japan, Philippines, South Korea, Taiwan, Thailand, Vietnam

Eetarp Power (M) Sdn Bhd

A-5-11, Blk Allamanda 10 Boulevard, Lebuhraya
Sprint PJU 6A 47400,
PJ, Selangor, Malaysia
Tel: +65 6339 3651
Fax: + 65 6339 3667
Email: contact@eetarp.com
CRN: 1205228P